Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



83932 Multi-Conductor - High-Temperature Thermocouple Extension Cable



For more Information please call

1-800-Belden1



General Description:

20 AWG solid conductors, FEP insulation, unshielded, FEP jacket.

Physical Characteristics (Overall)

AWG:

	# Conductors	AWG	Stranding	Conductor Material
ı	1	20	Solid	Chromel
ı	1	20	Solid	Alumel

Total Number of Conductors:

2

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
FEP - Fluorinated Ethylene Propylene	.010

Outer Shield

Outer Shield Material:



Outer Jacket

Outer Jacket Material:

Outer Jacket Material FEP - Fluorinated Ethylene Propylene

Overall Cable

Overall Nominal Diameter: 0.076 x 0.128 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-70°C To +200°C
Non-UL Temperature Rating:	200°C
Bulk Cable Weight:	13 lbs/1000 ft.
Min. Bend Radius/Minor Axis:	1.250 in.

PLTC CL3P

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(III.) Specification:

NEC/(OL) Specification.	FLTO, GLOF
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
ANSI Specification:	MC 96.1-1982 Type KX
Flame Test	

UL Flame Test: UL910 Steiner Tunnel

Plenum/Non-Plenum

Plenum (Y/N): Yes

> Page 1 of 2 07-21-2016

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



83932 Multi-Conductor - High-Temperature Thermocouple Extension Cable

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
CHROMEL	420
ALUMEL	169

Notes (Overall)

Notes: Chromel & Alumel = "Chromel and Alumel are Hoskins Manufacturing Company trademarks."

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83932 0041000	1,000 FT	14.000 LB	YELLOW	С	2#20TYPE KX THERMOCOUPLE

Notes: C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 06-29-2011

© 2016 Belden, Inc

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Page 2 of 2 07-21-2016